



This powerful bucket mounted sweeper converts a material handling bucket into a versatile sweeper collector unit. Three sweeper sizes are available to suit bucket internal widths ranging between 1.83 and 2.44m. Pick up lugs are welded to the bucket and the sweeper connected using a simple 'quick attach system'. Sweeping and collection is best carried out in reverse. The high torque hydraulic drive is reversible and fitted with a pressure relief valve to protect motor seals. Sprung loaded jack legs reduce bucket edge damage, noise and vibration. The unit has integrated parking stands for storage and servicing when not in use.

Model	Mount	Bucket width	Sweeping width	Overall width
BBX-SM	Bucket	1.83 - 2.03m	1.78m	2.17m
BBX-MED	Bucket	2.03 - 2.24m	1.98m	2.37m
BBX-LG	Bucket	2.24 - 2.44m	2.18m	2.57m

### Specification

- Use: Heavy – Extra heavy duty sweeping and collection.
- Mounting: Quick fit. Pick up lugs welded to customer bucket.
- Power Source: Hydraulic: 40 – 70 litres/min flow rate @ min 140 BAR.
- Brush Adjust: Heavy duty, sprung loaded jack legs.
- Brush Spec: 560mm diameter: poly, or poly/wire mix.
- Drive: Reversible high torque motor - relief valve protection.



- High torque direct drive motor.
- Relief valve motor protection.
- Reversible brush drive.
- Sprung loaded jack legs.
- Heavy duty steel construction.
- Single hydraulic service operation.
- Quick fit mounting system.
- Internal debris shroud.
- Parking/maintenance stands.
- Quick change brush.
- Choice of brush bristle.
- Choice of 3 sweeping widths.

